




APAG s.a.s. v. Stalingrado n°17 42015 Correggio (R.E.) Italy **03-2006**
 tel:+39-0522-633065 Fax:+39-0522-732934 e-mail: apag@apag.it www.apag.it

 **Applicazione:** ASPIRAZIONE E MANDATA

LIQUIDI.
 PARTICOLARMENTE INDICATO PER LIQUIDI
 ALIMENTARI, SOLUZIONI ALCOLICHE MAX 28%
 RESISTENTE ALL'ABRASIONE E ALL'OZONO.

Temperatura: -5°C / +60°C (+23°F / +140°F)

Norme: CEE 90/128 A+B+C. AS2070



 **Application:** ASPIRATION ET REFOULEMENT DE LIQUIDES ALIMENTAIRES EN PARTICULIER
 AVEC ALCOOL MAX 28%, RESISTANT A L'ABRASION ET AU AZOTE, AVEC RENFORCEMENTS EN PVC.

Température: -5°C / +60°C (+23°F / +140°F)

Norme: CEE 90/128 A+B+C. AS2070

 **Aplicación:** ASPIRACIÓN Y ENVÍO DE LÍQUIDOS ALIMENTARIO EN PARTICULAR CON
 ALCOHOL MAX 28%, RESISTENTE A ABRASIÓN Y AZOTO, CON REFUERZO EN PVC.


Temperatura: -5°C / +60°C (+23°F / +140°F)

Norma: CEE 90/128 A+B+C. AS2070

 **Application :** SUCTION AND SENT FOOD LIQUIDS, ALCOHOLICS SOLUTION TO 28%,
 RESISTANT TO ABRASION AND NITROGEN, WITH PVC SPRING.

Temperature: -5°C / +60°C (+23°F / +140°F)

Norms: CEE 90/128 A+B+C. AS2070

Codice	Ø interno	Press.Lavoro	Press.Scoppio	Peso	depressione	R.Min.Curvatura	Lungh. rotoli	Prezzo/mt.
Code	Ø inside	pressure of job	pressure of burst	Weight	vacum	min.ray of bending	length rolls	Price/mt.
ENO ⁽²⁵⁾								€
	mm.	bar	bar	gr./Mt.	Mt./H2O	mm.	Mt.	€
ENO 25	25	7	21	370	8,5	125	50	
ENO 30	30	7	21	470	8,5	150	50	
ENO 32	32	7	21	500	8	160	50	
ENO 38	38	7	21	650	8	190	50	
ENO 40	40	7	21	680	8	200	50	
ENO 51	51	7	21	1000	8	255	50	
ENO 60	60	7	21	1300	8	300	50	
ENO 63	63	6	18	1360	8	315	50	
ENO 70	70	5	15	1700	8	350	50	
ENO 76	76	5	15	1830	8	380	50	
ENO 80	80	5	15	1930	8	400	50	
ENO 102	102	4	12	2950	8	510	20	
ENO 120	120	3	9	4650	8	600	20	